

## Recovery unit VRR36C4



Refrigerants: kat. III	R12, R134a, R401C, R406A, R500, R1234yf
Refrigerants: kat. IV	R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R502, R509
Refrigerants: kat V	R402A, R404A, R407A, R407B, R410A, R507, R32
Power supply	230/50 V/Hz
Motor power	1,5 KM
Motor speed	3000 obr/min
Max current	5 A
Compressor	Tłokowa, chłodzona powietrzem, bezolejowa
Auto off	38,5/3850 bar/kPa (558 psi)
Recovery efficiency: kat. III - gas / liquid / push/pull	0,60 / 4,00 / 8,60 kg/min
Recovery efficiency: kat. IV - gaz / liquid / push/pull	0,80 / 4,50 / 9,80 kg/min

## Recovery unit VRR36C4

Recovery efficiency: kat. V - gaz / liquid / push/pull	0,8 5 / 4,65 / 11,00 kg/min
Teperature	0 ÷ 40 °C
Dimensions	410 x 275 x 300 mm
Weight	19 kg
Set	Shoulder strap, dry filter, 15 cm hose, ¼" x ¼", O.F.P. hose

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

---

## Recovery unit VRR36C4

---

Refrigerant recovery unit is used for the recovery of refrigerant HFC and HCFC.

The main features:

- rapid recovery of refrigerant
- little handy recovery unit
- equipped with a high and low pressure gauge
- manual reset

O.F.P. hose it is used for connection with cylinders overfill sensor.